
ROOFERS CHOICE

EAVES PROTECTION STRIP

Features

- Purpose made for eaves protection
- Tailor made roll size
- Durable – will last the life of the building
- Universal – can be used with all types of under-slating felt
- Rot-proof – will not deteriorate, even when wet for long periods
- NHBC recommended
- Manufactured to BS747 Type 5u

Roofers Choice Eaves Protection Strip is a high performance polyester (manufactured to BS747 Type 5u) sheet designed to give permanent protection where dressing an under-slating felt into an external gutter. It can be used with any under-slating materials (including breather membranes), any tile or slate finishes and in cold or warm roof configurations.

It is not always appreciated that many products used as under-slating materials, whilst satisfactory when covered by a tile or slate roof finish, have a limited life expectancy when exposed to UV light at roof edges. As such, when failure occurs water is allowed to run behind the gutter, rotting timber fascias and rafter ends. Repair of this damage is often difficult and costly.

The use of Roofers Choice Eaves Protection Strip will ensure long term performance of the under-slating in this location.

Application

Roofers Choice Eaves Protection Strip should be installed in accordance with the recommendations of BS 5534 : Part 1 : 1997 (Section 4.2.1.2) Code of Practice for Slating and Tiling. The Eaves Protection Strip is fixed as the first sheet along the eaves so it can be subsequently dressed over and inside the edge of the external gutter. The main under-slating sheets should then be laid horizontally up the roof from that point.

When installing under-slating, vertical laps should be a minimum of 100 mm and should be supported over a rafter. Horizontal laps will vary depending on the pitch of the roof and should be formed in accordance with the table set out below.

Roof Pitch	Horizontal Lap
12.5° - 14°	225mm
15° - 34°	150 mm
35° and above	100 mm

Product Details

Product Dimensions	Eaves Protection Strip
Roll Weight	9.66 kg
Roll Length	16 metres
Roll Width	0.33 mm

Mercury Building Products Limited
114 Eckington Road, Coal Aston
Dronfield S18 3AY



Mercury Building Products Limited
Unit 45, Station Lane Industrial Estate
Old Whittington, Chesterfield

Tel: 01246 292816 Fax: 01246 292867 Mobile: 07775 998148
e.mail : sales@ vapr-free.co.uk website: mercurybuildingproducts.com