

ROOFERS CHOICE 'light'

BREATHABLE UNDERLAY



Key Features

- Highly Water Resistant
- Breathable
- Eliminates Roof Space Ventilation
- Energy Saving
- User Friendly

Roofers Choice Light is a multi layer laminate film composite made of polyolefin materials, resulting in a pitched roof underlay that has high vapour permeability but is also highly water resistant.

Roofers Choice Light can be installed without the need for roof space ventilation (except for NHBC approved homes) and is suitable for both commercial and domestic buildings. It is the ideal roof underlay for warm and cold pitched roofs.

Manufactured without the use of CFC's Roofers Choice Light is 100% recyclable and is very durable with high tensile and nail tear strength properties. These, coupled with excellent UV and heat stability properties ensure a life-span in excess of 30 years.

Roofers Choice Light breathable membrane has received BBA Approval and complies with BS5534-2003 Code of Practice for slating and tiling and NFRCTB6. It also meets technical requirement R3 in relation to NHBC standards, chapter 7.2 pitched roofs.

Recommendations for the use of vapour permeable membranes in pitched roofs are contained in BS 5250 : 2002 'Code of practice for control of condensation in buildings'.

Quality Assurance



Head Office Tel: 01246 292816/FAX: 01246 292867
Warehouse Tel: 01246 268084/FAX: 01246 268094
Website: www.mercurybuildingproducts.com

Installation Guide

Non-Ventilated Cold Pitched Roofs (partially supported)

Roofers Choice Light when installed as a partially supported system should be fixed in the traditional method for roof tile underlays. Laid parallel to the eaves and **draped between the rafters** to ensure that any moisture reaching the underlay will drain away. It is held in place by the tile battens, fixed using staples or large headed nails. **Roofers Choice Light** can also be installed by pulling taut from gable to gable providing a 25mm counter batten is fixed to each rafter.

Prevention of Condensation

Roof space ventilation is not required providing the complete roof construction, ceiling boards, underlay, insulation and roof tiles are considered as a total roof system with regard to condensation risk. Insulation at ceiling level should be pressed tightly into the eaves against the underlay and all penetrations into, and out of, the roof space should be sealed. More extensive details of this can be found in our BBA certificate Section 5.

Prevention of Condensation (Extensions)

The roof space environment in both the extension and the original part of the dwelling should be the same. If the original part of the roof is vented then the extension should also be vented. Only if the extension is completely sealed off from the original roof should the **Roofers Choice Light** be installed without the aid of roof space ventilation.

Non-Ventilated Warm Pitched Roofs (fully supported)

Roofers Choice Light when fully supported by the insulation can be laid vertically or parallel to the eaves and **held in place using counter battens** (minimum height 25mm). These in conjunction with 25 mm tile battens will ensure a minimum 50 mm clear airway above the underlay and will assist natural air movement through the batten space. Battens should be fixed using staples or large headed nails.

Roof Space Ventilation

The NHBC require that for all New Build Homes, ridge or high level ventilation is installed when a vapour permeable membrane is used such as **Roofers Choice Light**. However, all other warm and cold pitched roofs do not require roof space ventilation when installed as recommended by this installation guide.

General

Roofers Choice Light must be installed with the (Grey) Printed side, face-up and overlapped with the minimum dimensions listed. Trimming is achieved with a sharp knife. When partially supported with a horizontal lap between battens an extra batten should be introduced 25mm above the bottom edge. This will restrain the lap from opening under wind uplift.

Roofers Choice Light prevents the ingress of wind driven rain and can be used as a temporary roof covering and left exposed to the elements. However it must be installed as recommended in our technical leaflet with regards to overlaps, fixings, draped between rafters or counter-battened and direct contact with uncured treated timber avoided.

Technical Data

Property	Units	Value
Weight	g/m ²	100
Water Vapour Resistance	Sd (M) MN/sg	c.0.02 0.15
Water Vapour Transmission	g/m ² /24 hr	1348
Fire Rating	-	B2*
Exposure Times UV Degradation	-	3/4 months

Product Data

Roll Width (linear metres)	1.0	1.0
Roll Length	25	50
Coverage/roll	25m ²	50m ²
Roll weight	2.5 kgs	5 kgs
Rolls/Pallet	40	56

Packaging and Storage

Roofers Choice Light is wrapped in polythene and delivered individually or palletised. Individual rolls should be stored on their sides on a clean, dry, flat surface and protected from direct sunlight.

Minimum Overlap Detail

Roof Pitch	Horizontal laps		Vertical Laps
	Partially Supported	Fully Supported	Either
12.5° to 14°	225	150	100
15° to 34°	150	100	100
35°	100	75	100

Detail	Minimum Overlap Horizontally and Vertically (mm)	
	Verge	25
Hips	150	
Ridge	150	
Valleys	300	
Eaves	25	

Eaves : Mercury Building Products strongly recommend the use of **VapR-free Underlay Support Trays** in both open and closed eave construction. Details of this unique versatile product can be obtained directly from Mercury Building Products or from one of our stockists.

Technical and Sales Support

Mercury Building Products Limited
114 Eckington Road, Coal Aston Dronfield S18 3AY
Tel: 01246 292816 Fax: 01246 292867

Unit 45, Station Lane Industrial Estate,
Old Whittington, Chesterfield
Tel: 07246 268084 Fax: 01246 268094

www.mercurybuildingproducts.com
email: sales@vaprfree.co.uk
email: danny@vaprfree.co.uk